




OIL CIRCULATING SYSTEMS



**CONFIGURABLE
STANDARD OCS**

A BRAND OF **BIJUR DELIMON**
INTERNATIONAL

**ROBUST
SYSTEMS
DESIGN**

**ENGINEERING
EXCELLENCE**

**MANUFACTURING
QUALITY**

**SERVICE
& SPARES**

CONFIGURABLE STANDARD OCS

Bijur Delimon International is a global supplier of Oil Circulating Systems and Equipment, designed for the optimum lubrication of bearings, gear trains and other processes requiring oil for lubrication and cooling.

- + A range of standard Multi-Purpose Oil Circulating units are manufactured to fill the need for a relatively simple, inexpensive, yet reliable system where a custom design is not required.
- + Reliability is a key to our success, achieved by utilizing proven design techniques, coupled with product quality and competitive pricing.



In providing the key functions of an Oil Circulating System, the system is built from the following primary equipment:

- **TANKS** – to allow settlement, de-aeration, and heating with the ability to condition and change the lubricant as appropriate.
- **PUMPS** – typically motor driven gear pumps to provide the correct flow and pressure to the application.
- **HEATERS & COOLERS** – to ensure the lubricant reaches the points of application at the required viscosity.
- **FILTRATION** – to maintain the system cleanliness at the required level.
- **INSTRUMENTATION** – monitoring for pressure, flow, filtration, temperature, and level.
- **ACCESSORIES** – controls and wiring, pressure relief.

SYSTEM DESIGN

One electric gear pump draws oil from a reservoir and supplies the oil via check valves through a single or dual basket type filter to the delivery connection.

Standard Units Comprised of:


- **RESERVOIR:** Fabricated from mild steel plate, sandblasted, and painted one coat primer with one coat of Light Grey (RAL7035).
- **RESERVOIR COMPONENTS:** Return and drain connections; level gauge; thermometer; air breather filler and filter.
- **PUMP & MOTOR:** Positive displacement integral gear type aluminum pump; 1500 rpm motor suitable for 380/440 VAC, 3phase, 50/60Hz supply.¹
- **OIL FILTER:** 25 μ (nominal) stainless steel mesh element; high dirt load capacity; visual/electrical clogging indication; bypass valves.¹
- **PRESSURE RELIEF VALVE:** Self-operating relief; easily adjustable relief spring pressure.
- **PRESSURE INDICATION:** 63mm gauge; 0-16 bar pressure.
- **CHECK VALVE, PIPE & FITTINGS:** Screwed, mild steel.
- **LEVEL SWITCH:** 2 position digital level switch.

¹ Standard design for oil viscosity up to ISO VG 220 - for higher viscosities, please contact our technical department.



OPTIONAL EXTRAS

- **HEATER:** 1kW, 3phase, 0.9W/cm² watts density; Thermostat.
- **PRESSURE TRANSMITTER:** 4-20mA analogue signal.
- **OIL COOLER:** Shell & Tube type; cooling oil to 100°F from 122°F with water at 68°F (water flow = oil flow x2).
- **ELECTRICAL:** Aluminum junction box.
- **FLOW SWITCH:** Viscosity compensating float type; SPDT contacts.
- **TANK TEMPERATURE:** PT100 RTD and Thermowell



CONFIGURABLE STANDARD OCS

Output (lpm)	Reservoir (liters)	Length (mm)	Width (mm)	Height (mm)	No. of Pumps	Filter	Connection	Return	Power (kW)	Part Number
5	50	515	345	405	1	Simplex	1/2" NPT thread	1" NPT thread	0.37	OF05010
						Duplex				OF05020
	100	760	500	505		Simplex				OF10010
						Duplex				OF10020
10	100	760	500	505	1	Simplex	1/2" NPT thread	1 1/4" NPT thread	0.55	OF10011
						Duplex				OF10021
	150	760	570	645		Simplex				OF15010
						Duplex				OF15020
15	150	760	570	645	1	Simplex	1/2" NPT thread	1 1/2" NPT thread	0.75	OF15011
						Duplex				OF15021
	350	1260	670	680		Simplex				OF35010
						Duplex				OF35020
20	250	1010	720	670	1	Simplex	3/4" NPT thread	1 1/2" NPT thread	1.1	OF25011
						Duplex				OF25021
	400	1250	745	720		Simplex				OF40010
						Duplex				OF40020
30	350	1260	670	680	1	Simplex	3/4" NPT thread	2" NPT thread	1.5	OF35011
						Duplex				OF35021
40	400	1250	745	720	1	Simplex	1" NPT thread	2" NPT thread	2.2	OF40011
						Duplex				OF40021
50	600	1360	860	800	1	Simplex	1" NPT thread	2" NPT thread	2.2	OF60010
						Duplex				OF60020

Option	Removable 1kW Heater + PT100 ¹	OF021E0000-1
Option	Wired Aluminum Junction Box	OF03JS0000
Option	Heat Exchanger + Thermostat 5LPM	OF04SP0000-1
Option	Heat Exchanger + Thermostat 5-40LPM	OF04SP0001-1
Option	Heat Exchanger + Thermostat 50LPM	OF04SP0002-1
Option	4-20 mA Pressure Transmitter	OF05TI0000
Option	Flow Meter + Control Needle Valve ¹	OF065K000-1
Option	Drip Pan (Available reservoir sizes: 50, 100, 150, 250, 350, 400, & 600 liters)	OF99CM (0+ tank volume)

¹ Max quantity of 2 in the standard design. If more heaters or flow meters are required, please contact our technical department.



Innovators of engineered lubrication technology since 1872

Bijur Delimon International has ISO 9001:2015 and ISO 14001:2015 quality certified manufacturing facilities around the world, so your centralized lubrication system meets the highest industry quality standards. It's all part of our commitment to quality and customer service.

OUR INDUSTRY LEADING FAMILY OF BRANDS



DELIMON

Farval®

 **LubeSite®**



USA

Bijur Delimon International
2685 Airport Road
Kinston, NC 28504

(252) 527-6001 TEL
(800) 227-1063 TOLL-FREE
(252) 527-9232 FAX

GERMANY

Delimon GmbH
Arminstrasse 15
40227 Düsseldorf

(+49) 211 / 77 74-0 TEL
(+49) 211 / 77 74-210 FAX

CHINA

Nanjing Bijur Machinery
Products, Ltd.
#9 Hengtong Road
Nanjing Xingang Economic &
Technical Development Zone
Nanjing 210038

(+86) 25-85801188 TEL
(+86) 25-85802288 FAX

UNITED KINGDOM

Denco Lubrication Limited
Ramsden Court
Ramsden Road
Rotherwas Industrial Estate
Hereford, HR2 6LR

(+44) (0) 1432365000 TEL
(+44) (0) 1432365001 FAX

IRELAND

Bijur Lubricating Ireland Limited
Gort Road
Ennis, County Clare

(+353) 6568-21543 TEL
(+353) 6568-29667 FAX

FRANCE

Bijur Products, Inc.
PB 50 - 9 Avenue du Quebec
ZI de Courtabœuf
Villebon Sur Yvette
F-91942 Courtaboeuf Cedex

(+33) (0)169298585 TEL
(+33) (0)169077627 FAX

SPAIN

Bijur Delimon International
- Lubrimonsa
Avenida Txorierrri 38
48150, Sondika, Bizkaia

(+34) 94-453-2000 TEL
(+34) 94-453-2500 FAX

INDIA

Bijur Delimon India Private Limited
Gat No. 448/13, Village Nigoje
Behind Mahindra Plant - Gate No. 8A
Taluka-Rajgurunagar (Khed)
District-Pune, Pin: 410 501
Maharashtra

(+91) 2032319149 TEL
(+91) 2027451725 FAX